



## 13" BLACK Spoke Radial Assembly

13" BLACK Spoke Radial Assembly

[Read More](#)

**SKU:** Y810300

**Categories:** [13"](#)

### Product Description

- **TIRE SPECS**

- ST175/80R13 C ply
- B78x13 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Radial Ply
- Load Range C, 1360# capacity
- S.W: 6.6" •O.D: 24.0"
- Max PSI 50
- Rim 13x4.5
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

- **Rim Specs**

- 13"x4.5" Black Spoke Steel Rim Painted
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1660# / 65PSI
- 0 offset
- 3.19" Pilot Diameter

---



## 13" GALVANIZED SPOKE Wheel BIAS Assemblies

CHOOSE TIRE SIZE AND BOLT PATTERN FROM DROP DOWN  
LIST

[Read More](#)

**SKU:** 13" GALVANIZED SPOKE Wheel Bias Assemblies

**Categories:** [13"](#)

### Product Description

- **Tire Spec OPTIONS:**
  - ST175/80D13 B ply
  - B78x13 Alternate Size
  - High Speed Trailer Tire
  - Tubeless type
  - Bias Ply
  - Load Range B, 1100# capacity
  - S.W: 6.5" •O.D: 23.9"
  - Max PSI 35
  - Rim 13x4.5
  - The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
  - These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
  - 
  - ST175/80D13 C ply
  - B78x13 Alternate Size
  - High Speed Trailer Tire
  - Tubeless type
  - Bias Ply
  - Load Range C, 1360# capacity
  - S.W: 6.6" •O.D: 24.0"
  - Max PSI 50
  - Rim 13x4.5
  - The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
  - These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
  - 
  - ST175/80D13 D ply

- B78x13 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias Ply
- Load Range D, 1610# capacity
- S.W: 6.6" •O.D: 24.0"
- Max PSI 65
- Rim 13x4.5
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- 
- ST185/80D13 Cply
- C78x13 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Bias Ply
- Load Range C, 1480# capacity
- S.W: 7.2" •O.D: 24.4"
- Max PSI 50
- Rim 13x4.5
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- 
- ST185/80D13 Dply
- C78x13 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Bias Ply
- Load Range D, 1725# capacity
- S.W: 7.2" •O.D: 24.4"
- Max PSI 65
- Rim 13x4.5
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

#### • **Rim Specs OPTIONS**

- 13"x4.5" Galvanized Spoke Steel Rim
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1660# / 65PSI
- 0 offset
- 3.19" Pilot Diameter

- Rim Specs
- 13"x4.5" Galvanized Spoke Steel Rim
- Bolt Pattern 4 x 4"
- Rim Capacity & PSI 1660# / 65PSI
- 0 offset
- 2.84" Pilot Diameter



## 13" ST175/80D13 BLACK Modular Hole Bias Assembly

13" BLACK Spoke BIAS PLY Assembly

[Read More](#)

**SKU:** Y810300

**Categories:** [13"](#)

### Product Description

- FACTORY 13" WHEEL ASSEMBLY ON CURRENT ANGLE STYLE UTILITY TRAILERS
- **TIRE SPECS**
  - ST175/80D13 C ply
  - B78x13 Alternate Size
  - High Speed Trailer Tire
  - Tubeless type
  - Bias Ply
  - Load Range C, 1360# capacity
  - S.W: 6.6" •O.D: 24.0"
  - Max PSI 50
  - Rim 13x4.5
- **Rim Specs**
  - 13"x4.5" Black Modular Hole Steel Rim Painted
  - Bolt Pattern 5 x 4.5"
  - Rim Capacity & PSI 1660# / 65PSI
  - 0 offset
  - 3.19" Pilot Diameter



## 13" ST175/80D13 SILVER Modular Hole Bias Assembly

13" SILVER MOD BIAS PLY Assembly

[Read More](#)

**SKU:** Y810300-1

**Categories:** [13"](#)

### Product Description

- **TIRE SPECS**

- ST175/80D13 C ply
- B78x13 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias Ply
- Load Range C, 1360# capacity
- S.W: 6.6" •O.D: 24.0"
- Max PSI 50
- Rim 13x4.5

- **Rim Specs**

- 13"x4.5" SILVER Modular Hole Steel Rim Painted
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1660# / 65PSI
- 0 offset
- 3.19" Pilot Diameter

---



## **13" ST175/80R13 Silver Mod Radial Assembly**

13" Silver Mod Radial Assembly

[Read More](#)

**SKU:** Y810090

**Categories:** [13"](#)

### **Product Description**

- TIRE SPECS**

- ST175/80R13 C ply
- B78x13 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Radial Ply
- Load Range C, 1360# capacity
- S.W: 6.6" •O.D: 24.0"
- Max PSI 50
- Rim 13x4.5
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

- Rim Specs**

- 13"x4.5" Silver Mod Steel Rim Painted
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1660# / 65PSI
- 0 offset
- 3.19" Pilot Diameter