



ELEVATE ST225/75R15 6H/D ply Silver Mod Trailer Wheel Assembly

ELEVATE ST225/75R15 6H/D ply Silver Mod Hole Radial Trailer Wheel Assembly

[Read More](#)

SKU: Y306130

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL**
- **ELEVATE ST225/75R15 Dply (8 PLY)**
- H78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Radial Ply
- Load Range D, 2540# capacity
- S.W: 8.9"
- O.D: 28.4"
- Max PSI 65
- Rim 15x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

-
-
-

- Rim Specs
- 15"x6" SILVER MOD HOLE Steel Rim Powder Coated
- Bolt Pattern 6 x 5.5"
- Rim Capacity & PSI 2830# / 80PSI
- 0 offset
- 4.27" Pilot Diameter



ELEVATE STR RADIAL ST205/75R15 Aluminum / Gun Metal Wheel Assembly 5H x 4.5" BP

15" Aluminum / Gun Metal Wheel / Tire Assembly 5H x 4.5" BP

[Read More](#)

SKU: Y305009-053

Categories: [15"](#)

Product Description

- Tire Specs
- Radial Ply
- ST205/75R15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Speed Rating M / 81 Mph
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- Wide center rib for improved road contact
- Open shoulder tread pattern to improve self-cleaning abilities
- Enhanced tread blade design to reduce scrubbing when turning
- Improved heat dissipation to extend the tread life
- Down To Earth Factory OEM Tire.

- Rim Specs:
-

- 15"x5" 1 Piece Aluminum
- Clear Coated Rim
- Bolt Pattern 5 x 4.5"
- Pilot Diameter 3.19"
- Rim Capacity 2150#
- 0 offset
- 5) Acorn Lug Nuts
- 1) Center Cap



GOODRIDE Bias ST205/75D15 5H/C ply Gloss BLACK MOD HOLE Trailer Wheel Assembly

GOODRIDE ST205/75D15 5H/C ply Gloss BLACK MOD HOLE Bias
Trailer Wheel Assembly !

[Read More](#)

SKU: D2E9400303-TT-1

Categories: [15"](#)

Product Description

- **Tire Specs**
- **BIAS PLY**
- GOODRIDE ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 8.1"
- O.D. 27.3"
- Max PSI 50
- RIM 15x5.5
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- Down To Earth Factory OEM Tire.
-
-

-
- **Rim Specs**
- 15"x5" BLACK Spoke Steel Rim, Powder Coated
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



GOODRIDE Radial ST205/75R15 5H/C ply Gloss BLACK Trailer Wheel Assembly

D2E9400303-TT : GOODRIDE ST205/75R15 5H/C ply Gloss BLACK Radial Trailer Wheel Assembly !

[Read More](#)

SKU: D2E9400303-TT

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL**
- GOODRIDE LOADSTAR KARRIER ST205/75R15 C ply (6 ply)
- F78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 8.1"
- O.D. 27.3"
- Max PSI 50
- RIM 15x5.5
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 5 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.

-
-
-
- **Rim Specs**
- 15"x5" BLACK Spoke Steel Rim, Powder Coated
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



GOODRIDE Radial ST225/75R15 6H/D ply Gloss BLACK MOD Trailer Wheel Assembly

D2E9400407-TT : LoadStar ST225/75R15 6H/D ply Gloss BLACK MOD HOLE Radial Trailer Wheel Assembly !

[Read More](#)

SKU: D2E9400407-TT

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL**
- **GOODRIDE RADIAL ST225/75R15 Dply (8 PLY)**
- H78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Radial Ply
- Load Range D, 2540# capacity
- S.W: 8.9"
- O.D: 28.4"
- Max PSI 65
- Rim 15x6
- The GOODRIDE Trailer tire provides a 5 year warranty with the warranty number imprinted on each tire.

- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Rim Specs
- 15"x6" Black Mod Hole Steel Rim Powder Coated
- Bolt Pattern 6 x 5.5"
- Rim Capacity & PSI 2830# / 80PSI
- 0 offset
- 4.27" Pilot Diameter



KENDA LOADSTAR K550 ST205/75D15 Aluminum 5 Star Wheel / Tire Assembly 5H x 4.5" BP

15" Aluminum 5 Star Wheel / Tire Assembly 5H x 4.5" BP !

[Read More](#)

SKU: D2E3S649

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.
 - Rim Specs:
- - 15"x6" 1 Piece Aluminum
 - Clear Coated Rim

- Bolt Pattern 5 x 4.5"
- Pilot Diameter 3.19"
- Rim Capacity 2150#
- 0 offset



KENDA LOADSTAR K550 ST205/75D15 Aluminum 7 Star Wheel / Tire Assembly 5H x 4.5" BP

15" Aluminum 7 Star Wheel / Tire Assembly 5H x 4.5" BP

[Read More](#)

SKU: D2E3S264

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.
 - Rim Specs:
- - 15"x6" 1 Piece Aluminum
 - Clear Coated Rim
 - Bolt Pattern 5 x 4.5"
 - Pilot Diameter 3.19"
 - Rim Capacity 2150#
 - 0 offset



KENDA LOADSTAR K550 ST205/75D15 Aluminum Split Spoke Wheel / Tire Assembly 5H x 4.5" BP

15" Aluminum Split Spoke Wheel / Tire Assembly 5H x 4.5" BP

[Read More](#)

SKU: D2E3S740HWT

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.
 - Rim Specs:
- - 15"x6" 1 Piece Aluminum
 - Clear Coated Rim
 - Bolt Pattern 5 x 4.5"
 - Pilot Diameter 3.19"
 - Rim Capacity 2150#
 - 0 offset



KENDA LOADSTAR K550 ST205/75D15 5H on 4.5" C ply MODULAR HOLE ALUMINUM Trailer Wheel Assembly

D2E3S644 : LoadStar K550 Bias ST205/75D15 5H on 4.5" C ply
MODULAR HOLE ALUMINUM Trailer Wheel Assembly

[Read More](#)

SKU: D2E3S644

Categories: [15"](#)

Product Description

- **Tire Specs:**

- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- • High Speed Trailer Tire
- • Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.6"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.

- **Rim Specs:**

- 15"x6" 1 Piece Aluminum MOD HOLE
- Clear Coated Rim
- Bolt Pattern 5 x 4.5"
- Pilot Diameter 3.19"
- Rim Capacity 2150#
- 0 offset



KENDA LOADSTAR K550 ST205/75D15 5Hon5"/C ply White Spoke Trailer Wheel Assembly

LoadStar K550 ST205/75D15 Cply mounted to 15"x5" White Spoke Rim featuring 5 on 5" Bolt Pattern.

[Read More](#)

SKU: D2E3S638

Categories: [15"](#)

Product Description

- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.
- Rim Specs
- 15"x5" White Spoke Steel Rim Powder Coated w/ Red/Blue Pinstripe &
- Bolt Pattern 5 x 5"
- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



KENDA LOADSTAR K550 ST205/75D15 BLACK Spoke 5Hx4.5/C Assembly

KENDA LOADSTAR K550 ST205/75D15 BLACK Spoke 5Hx4.5/C
Assembly

[Read More](#)

SKU: D2E3S651

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.

- Rim Specs
- 15"x5" BLACK Spoke Steel Rim, Powder Coated
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



KENDA LOADSTAR K550 ST205/75D15 Galvanized Trailer Wheel / Tire Assembly 5H x 4.5" Cply

15" Galvanized Trailer Wheel / Tire Assembly 5H x 4.5" Cply

[Read More](#)

SKU: D2E3S650

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 65
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.

- Rim Specs
- 15"x6" Galvanized Spoke Steel Rim
- Rim Capacity & PSI 2050# @ 75 PSI
- 0 offset
- 3.19" Pilot Diameter



KENDA LOADSTAR K550 ST205/75D15 Silver Mod 5HOn5" /C Assembly

D2E32253 : Loadstar K550 ST205/75D15 Silver Mod 5HOn5"/C
Assembly

[Read More](#)

SKU: D2E32253

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.

- Rim Specs
- 15"x5" Silver Modular Hole Steel Rim, Powder Coated
- Bolt Pattern 5 x 5"
- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



KENDA LOADSTAR K550 ST205/75D15 Silver Mod 5Hx4.5/C Assembly

D2E3S636 : Loadstar K550 ST205/75D15 Silver Mod 5Hx4.5/C Assembly

[Read More](#)

SKU: D2E3S636

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.

- Rim Specs
- 15"x5" Silver Modular Hole Steel Rim, Powder Coated
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



KENDA LOADSTAR K550 ST205/75D15 White Mod 5Hx4.5/C Assembly

D2E3S636 : Loadstar K550 ST205/75D15 White Mod 5Hx4.5/C Assembly

[Read More](#)

SKU: D2E3S645

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.

- Rim Specs
- 15"x5" White Modular Hole Steel Rim, Powder Coated
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1820# / 50PSI

- 0 offset
- 3.19" Pilot Diameter



KENDA LOADSTAR K550 ST225/75D15 6Hon5.5"/D ply FIVE STAR ALUMINUM Trailer Wheel Assembly

D2E3S913 : LoadStar K550 Bias ST225/75D15 6Hon5.5"/D ply
FIVE STAR ALUMINUM Trailer Wheel Assembly

[Read More](#)

SKU: D2E3S913

Categories: [15"](#)

Product Description

- **TIRE SPECS:**
- KENDA LOADSTAR K550 ST225/75D15 Dply
- H78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Bias Ply
- Load Range D, 2540# capacity
- S.W: 8.4"
- O.D: 28.1"
- Max PSI 65
- Rim 15x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

- **RIM SPECS:**

- 15"x6" 1 Piece Aluminum
- Clear Coated Rim
- Bolt Pattern 6 x 5.5"
- Pilot Diameter 4.25"
- Rim Capacity 2830#
- 0 offset



KENDA LOADSTAR K550 ST225/75D15 BLACK Spoke 6Hx5.5/D Assembly

KENDA LOADSTAR K550 ST225/75D15 BLACK Spoke 6Hx5.5/D Assembly !

[Read More](#)

SKU: D2E3S878

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550
- ST225/75D15 Dply
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- H78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Bias Ply
- Load Range D, 2540# capacity
- S.W: 8.4"
- O.D: 28.1"
- Max PSI 65
- Rim 15x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements. Down To Earth Factory OEM Tire.

- Rim Specs
- 15"x6" BLACK Spoke Steel Rim Powder Coated
- Bolt Pattern 6 x 5.5"
- Rim Capacity & PSI 2830# / 80PSI
- 0 offset
- 4.27" Pilot Diameter



KENDA LOADSTAR K550 ST225/75D15 Silver Modular Hole 6Hx5.5/D Assembly

KENDA LOADSTAR K550 ST225/75D15 Silver Modular Hole
6Hx5.5/D Assembly

[Read More](#)

SKU: D2E3S918

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550
- ST225/75D15 Dply
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- H78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Bias Ply
- Load Range D, 2540# capacity
- S.W: 8.4"
- O.D: 28.1"
- Max PSI 65
- Rim 15x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements. Down To Earth Factory OEM Tire.

- Rim Specs
- 15"x6" Silver Modular Hole Steel Rim, Powder Coated
- Bolt Pattern 6 x 5.5"
- Rim Capacity & PSI 2830# / 80PSI
- 0 offset
- 4.27" Pilot Diameter



KENDA LOADSTAR K550 ST225/75D15 White Spoke 5Hx4.5/D Assembly

KENDA LOADSTAR K550 ST225/75D15 White Spoke 5Hx4.5/D
Assembly Free Shipping

[Read More](#)

SKU: D2E3S862

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550
- ST225/75D15 Dply
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- H78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Bias Ply
- Load Range D, 2540# capacity
- S.W: 8.4"
- O.D: 28.1"
- Max PSI 65
- Rim 15x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements. Down To Earth Factory OEM Tire.

- Rim Specs
- 15"x6" White Spoke Steel Rim Powder Coated w/ Red/Blue Pinstripe &
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 2050# / 75 PSI
- 0 offset
- 3.19" Pilot Diameter



KENDA LOADSTAR K550 ST225/75D15 White Spoke 6Hx5.5/D Assembly

KENDA LOADSTAR K550 ST225/75D15 White Spoke 6Hx5.5/D Assembly

[Read More](#)

SKU: D2E3S870

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550
- ST225/75D15 Dply
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- H78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Bias Ply
- Load Range D, 2540# capacity
- S.W: 8.4"
- O.D: 28.1"
- Max PSI 65
- Rim 15x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements. Down To Earth Factory OEM Tire.

- Rim Specs
- 15"x6" White Spoke Steel Rim Powder Coated w/ Red/Blue Pinstripe &
- Bolt Pattern 6 x 5.5"
- Rim Capacity & PSI 2830# / 80PSI
- 0 offset
- 4.27" Pilot Diameter



LoadStar KARRIER Radial ST205/75R15 5H/C ply Gloss BLACK Trailer Wheel Assembly

D2E32407 : LoadStar ST205/75R15 5H/C ply Gloss BLACK Radial
Trailer Wheel Assembly !

[Read More](#)

SKU: D2E32407

Categories: [15"](#)

Product Description

- **Tire Specs**

- **RADIAL**

- KENDA LOADSTAR KARRIER ST205/75R15 C ply (6 ply)
- F78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 8.1"
- O.D. 27.3"
- Max PSI 50
- RIM 15x5.5
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.
-
-
-

- **Rim Specs**

- 15"x5" BLACK Spoke Steel Rim, Powder Coated
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



LoadStar Karrier Radial ST225/75R15 5H/D ply Gloss WHITE Trailer Wheel Assembly

D2E32545 : LoadStar ST225/75R15 5H/D ply Gloss WHITE Radial
Trailer Wheel Assembly !

[Read More](#)

SKU: D2E32545

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL**
- **KENDA LOADSTAR KARRIER ST225/75R15 Dply (8 PLY)**
- H78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Radial Ply
- Load Range D, 2540# capacity
- S.W: 8.9"
- O.D: 28.4"
- Max PSI 65
- Rim 15x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
-
-
-
- Rim Specs

- 15"x6" WHITE Spoke Steel Rim Powder Coated w/ Red/Blue Pinstripe
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 2050# / 75PSI
- 0 offset
- 3.19" Pilot Diameter



LoadStar Karrier Radial ST225/75R15 6H/D ply Gloss BLACK Trailer Wheel Assembly

D2E32566 : LoadStar ST225/75R15 6H/D ply Gloss BLACK Radial
Trailer Wheel Assembly !

[Read More](#)

SKU: D2E32566

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL**
- **KENDA LOADSTAR KARRIER ST225/75R15 Dply (8 PLY)**
- H78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Radial Ply
- Load Range D, 2540# capacity
- S.W: 8.9"
- O.D: 28.4"
- Max PSI 65
- Rim 15x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
-

-
-
- Rim Specs
- 15"x6" Black Spoke Steel Rim Powder Coated
- Bolt Pattern 6 x 5.5"
- Rim Capacity & PSI 2830# / 80PSI
- 0 offset
- 4.27" Pilot Diameter



Radial ST205/75R15 5H/C ply Galvanized Trailer Wheel Assembly

32397 : LoadStar Karrier Radial ST205/75R15 5H/C ply
Galvanized Trailer Wheel Assembly !

[Read More](#)

SKU: D2E32397

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL ST205/75R15 C ply (6 ply)**
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 8.1"
- O.D. 27.3"
- Max PSI 50
- RIM 15x5.5
- Steel Belted Constructed Tire for Smooth Ride and Increased Tread Wear.
-
- **Rim Specs**

- 15"x5" Galvanized Spoke Steel Rim
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



Radial ST205/75R15 5H/C ply Silver Mod Trailer Wheel Assembly

ST205/75R15 5H/C ply SILVER MOD Radial Trailer Wheel Assembly!

[Read More](#)

SKU: Y305110

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL**
- ST205/75R15 C ply (6 ply)
- F78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 8.1"
- O.D. 27.3"

- Max PSI 50
- RIM 15x5.5
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.
-
-
-
-
- **Rim Specs**
- 15"x5" Silver Mod Hole Steel Rim Powder Coated
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



Radial ST225/75R15 6H/D ply Gloss BLACK MOD Trailer Wheel Assembly

D2E32566 : LoadStar ST225/75R15 6H/D ply Gloss BLACK MOD HOLE Radial Trailer Wheel Assembly !

[Read More](#)

SKU: D2E33043

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL**
- **KENDA LOADSTAR KARRIER ST225/75R15 Dply (8 PLY)**
- H78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Radial Ply

- Load Range D, 2540# capacity
- S.W: 8.9"
- O.D: 28.4"
- Max PSI 65
- Rim 15x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
-
-
-
- Rim Specs
- 15"x6" Black Mod Hole Steel Rim Powder Coated
- Bolt Pattern 6 x 5.5"
- Rim Capacity & PSI 2830# / 80PSI
- 0 offset
- 4.27" Pilot Diameter



RANIER Radial ST205/75R15 5H/C ply SILVER MOD Trailer Wheel Assembly

RANIER ST205/75R15 5H/C ply SILV MOD Radial Trailer Wheel Assembly

[Read More](#)

SKU: D2E9400303M-TT-1

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL**

- RANIER ST205/75R15 C ply (6 ply)
- F78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 8.1"
- O.D. 27.3"
- Max PSI 50
- RIM 15x5.5
-
- **Rim Specs**
- 15"x5" SILVER MODULAR HOLE Steel Rim, Powder Coated
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



RANIER Radial ST205/75R15 5H/C ply SILVER MOD Trailer Wheel Assembly

RANIER ST205/75R15 5H/C ply SILV MOD Radial Trailer Wheel Assembly

[Read More](#)

SKU: D2E9400303M-TT-1-2

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL**
- RANIER ST205/75R15 C ply (6 ply)
- F78x15 Alternate Size
- •High Speed Trailer Tire

- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 8.1"
- O.D. 27.3"
- Max PSI 50
- RIM 15x5.5
-
- **Rim Specs**
- 15"x5" SILVER MODULAR HOLE Steel Rim, Powder Coated
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



Spare Tire Mount for D2E Non-Dump Trailers 3.5K & 5.2K, fits 5 & 6 Lug Bolt Pattern

Weld-on HD Steel Spare Tire Mount for 7K & 10K Non-Dump Trailers

Fits 5x4.5" & 6x5.5" lug pattern

[Read More](#)

SKU: 17.5STBND-1

Categories: [15"](#), [Spare Tire Mounting Systems](#)

Product Description

This is a weld-on HD Steel Spare Tire Mount for 7K & 10K Non-Dump Trailers

Fits 5x4.5" & 6x5.5" lug pattern

Used on Car Haulers, Utility, Equipment Trailers

Direct weld on for Dump Trailers made by Down To Earth Trailers

Includes (2) 1/2" Lug Studs & Nuts to mount wheel



ST205/75D15 White Spoke 5Hx4.5/C Assembly

KENDA LOADSTAR K550 ST205/75D15 White Spoke 5Hx4.5/C Assembly

[Read More](#)

SKU: D2E3S640

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.

- Rim Specs
- 15"x5" White Spoke Steel Rim Powder Coated w/ Red/Blue Pinstripe &
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1820# / 50PSI

- 0 offset
- 3.19" Pilot Diameter



ST205/75R15 Aluminum T07/BM Wheel / Tire Assembly 5H x 4.5" BP

15" RADIAL Aluminum Split Spoke Wheel / Tire Assembly 5H x 4.5" BP T07 in Gloss Black

[Read More](#)

SKU: D2ET07

Categories: [15"](#)

Product Description

- INCLUDES SS CAP AND ACORN LUG NUTS, NOT SHOWN.
-
- Tire Specs
- ST205/75R15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- RADIAL Ply Constructed Tire for Smooth Ride and Longevity.
 - Rim Specs:
 - 15"x6" 1 Piece Aluminum
 - T07 in Gloss Black
 - Clear Coated Rim
 - Bolt Pattern 5 x 4.5"
 - Pilot Diameter 3.19"
 - Rim Capacity 2150#
 - 0 offset



ST225/75R15 6H/E ply EDGE Aluminum Trailer Wheel Assembly w/ Caps/Nuts

ST225/75R15 6H/E ply Edge Alum Radial Trailer Wheel Assembly

[Read More](#)

SKU: Y30613-1

Categories: [15"](#)

Product Description

Complete Assembly including Stainless Center Cap and (6) Acorn Lug Nuts

- **Tire Specs**
- **RADIAL**
- **ST225/75R15 Eply (10 PLY)**
- H78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Radial Ply
- Load Range E, 2860# capacity
- S.W: 8.9"
- O.D: 28.4"
- Max PSI 80
- Rim 15x6
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
-
-
-
- Rim Specs
- 15"x6"Aluminum w/ Black Inlay
- Bolt Pattern 6 x 5.5"
- Rim Capacity & PSI 2830# / 80PSI
- 0 offset
- 3.75" Pilot Diameter

