



13" BLACK Spoke Radial Assembly

13" BLACK Spoke Radial Assembly

[Read More](#)

SKU: Y810300

Categories: [13"](#)

Product Description

- **TIRE SPECS**

- •ST175/80R13 C ply
- •B78x13 Alternate Size
- •High Speed Trailer Tire
- •Tubeless type
- •Radial Ply
- •Load Range C, 1360# capacity
- •S.W: 6.6" •O.D: 24.0"
- •Max PSI 50
- •Rim 13x4.5
- •The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- •These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

- **Rim Specs**

- 13"x4.5" Black Spoke Steel Rim Painted
 - Bolt Pattern 5 x 4.5"
 - Rim Capacity & PSI 1660# / 65PSI
 - 0 offset
 - 3.19" Pilot Diameter
-



13" GALVANIZED SPOKE Wheel BIAS Assemblies

CHOOSE TIRE SIZE AND BOLT PATTERN FROM DROP DOWN LIST

[Read More](#)

SKU: 13" GALVANIZED SPOKE Wheel Bias Assemblies

Categories: [13"](#)

Product Description

- **Tire Spec OPTIONS:**
 - ST175/80D13 B ply
 - B78x13 Alternate Size
 - High Speed Trailer Tire
 - Tubeless type
 - Bias Ply
 - Load Range B, 1100# capacity
 - S.W: 6.5" •O.D: 23.9"
 - Max PSI 35
 - Rim 13x4.5
 - The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
 - These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- - ST175/80D13 C ply
 - B78x13 Alternate Size
 - High Speed Trailer Tire
 - Tubeless type
 - Bias Ply
 - Load Range C, 1360# capacity
 - S.W: 6.6" •O.D: 24.0"
 - Max PSI 50
 - Rim 13x4.5
 - The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
 - These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- - ST175/80D13 D ply

- •B78x13 Alternate Size
- •High Speed Trailer Tire
- •Tubeless type
- •Bias Ply
- •Load Range D, 1610# capacity
- •S.W: 6.6" •O.D: 24.0"
- •Max PSI 65
- •Rim 13x4.5
- •The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- •These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

•

- •ST185/80D13 Cply
- •C78x13 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- •Bias Ply
- •Load Range C, 1480# capacity
- •S.W: 7.2" •O.D: 24.4"
- •Max PSI 50
- •Rim 13x4.5
- •The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- •These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

•

- •ST185/80D13 Dply
- •C78x13 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- •Bias Ply
- •Load Range D, 1725# capacity
- •S.W: 7.2" •O.D: 24.4"
- •Max PSI 65
- •Rim 13x4.5
- •The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- •These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

- **Rim Specs OPTIONS**

- 13"x4.5" Galvanized Spoke Steel Rim
- Bolt Pattern 5 x 4.5"
- Rim Capacity & PSI 1660# / 65PSI
- 0 offset
- 3.19" Pilot Diameter

- Rim Specs
 - 13"x4.5" Galvanized Spoke Steel Rim
 - Bolt Pattern 4 x 4"
 - Rim Capacity & PSI 1660# / 65PSI
 - 0 offset
 - 2.84" Pilot Diameter
-



13" ST175/80D13 BLACK Modular Hole Bias Assembly

13" BLACK Spoke BIAS PLY Assembly

[Read More](#)

SKU: Y810300

Categories: [13"](#)

Product Description

- FACTORY 13" WHEEL ASSEMBLY ON CURRENT ANGLE STYLE UTILITY TRAILERS
 - **TIRE SPECS**
 - ST175/80D13 C ply
 - B78x13 Alternate Size
 - High Speed Trailer Tire
 - Tubeless type
 - Bias Ply
 - Load Range C, 1360# capacity
 - S.W: 6.6" •O.D: 24.0"
 - Max PSI 50
 - Rim 13x4.5
 - **Rim Specs**
 - 13"x4.5" Black Modular Hole Steel Rim Painted
 - Bolt Pattern 5 x 4.5"
 - Rim Capacity & PSI 1660# / 65PSI
 - 0 offset
 - 3.19" Pilot Diameter
-



13" ST175/80D13 SILVER Modular Hole Bias Assembly

13" SILVER MOD BIAS PLY Assembly

[Read More](#)

SKU: Y810300-1

Categories: [13"](#)

Product Description

- **TIRE SPECS**

- •ST175/80D13 C ply
- •B78x13 Alternate Size
- •High Speed Trailer Tire
- •Tubeless type
- •Bias Ply
- •Load Range C, 1360# capacity
- •S.W: 6.6" •O.D: 24.0"
- •Max PSI 50
- •Rim 13x4.5

- **Rim Specs**

- 13"x4.5" SILVER Modular Hole Steel Rim Painted
 - Bolt Pattern 5 x 4.5"
 - Rim Capacity & PSI 1660# / 65PSI
 - 0 offset
 - 3.19" Pilot Diameter
-



13" ST175/80R13 Silver Mod Radial Assembly

13" Silver Mod Radial Assembly

[Read More](#)

SKU: Y810090

Categories: [13"](#)

Product Description

- **TIRE SPECS**

- •ST175/80R13 C ply
- •B78x13 Alternate Size
- •High Speed Trailer Tire
- •Tubeless type
- •Radial Ply
- •Load Range C, 1360# capacity
- •S.W: 6.6" •O.D: 24.0"
- •Max PSI 50
- •Rim 13x4.5
- •The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- •These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

- **Rim Specs**

- 13"x4.5" Silver Mod Steel Rim Painted
 - Bolt Pattern 5 x 4.5"
 - Rim Capacity & PSI 1660# / 65PSI
 - 0 offset
 - 3.19" Pilot Diameter
-



205/65-10 Galvanized 4H/C ply Assembly

3H380 : 205/65-10 Galvanized 4H/C ply Assembly FREE SHIPPING to 48 Continental US States!!!!

[Read More](#)

SKU: 3H380

Categories: [10"](#)

Product Description

- ST205/65-10 C ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias 6 Ply
- Load Range C, 1100# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 50
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6" Galvanized Finish
 - 0 offset
 - 4H x 4" Bolt Pattern
-



205/65-10 Galvanized 4H/D ply Assembly

3H420 : 205/65-10 Galvanized 4H/D ply Assembly FREE SHIPPING to 48 Continental US States!!!!

[Read More](#)

SKU: 3H420

Categories: [10"](#)

Product Description

- ST205/65-10 D ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias8 Ply
- Load Range D, 1330# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 70
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6" Galvanized Finish
 - 0 offset
 - 4H x 4" Bolt Pattern
-



205/65-10 Galvanized 4H/Eply Assembly

3H470 : 205/65-10 Galvanized 4H/Eply Assembly FREE SHIPPING
to 48 Continental US States!!!!

[Read More](#)

SKU: 3H470

Categories: [10"](#)

Product Description

- ST205/65-10 E ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias10 Ply
- Load Range E, 1660# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 90
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6" Galvanized Finish
 - 0 offset
 - 4H x 4" Bolt Pattern
-



205/65-10 Galvanized 5H/C ply Assembly

3H400 : 205/65-10 Galvanized 5H/C ply Assembly FREE SHIPPING to 48 Continental US States!!!!

[Read More](#)

SKU: 3H400

Categories: [10"](#)

Product Description

- ST205/65-10 C ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias 6 Ply
- Load Range C, 1100# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 50
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6" Galvanized Finish
 - 0 offset
 - 5H x 4.5" Bolt Pattern
-



205/65-10 Galvanized 5H/D ply Assembly

3H440 : 205/65-10 Galvanized 5H/D ply Assembly FREE SHIPPING to 48 Continental US States!!!!

[Read More](#)

SKU: 3H440

Categories: [10"](#)

Product Description

- ST205/65-10 D ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias8 Ply
- Load Range D, 1330# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 70
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6" Galvanized Finish
 - 0 offset
 - 5H x 4.5" Bolt Pattern
-



205/65-10 Galvanized 5H/Eply Assembly

3H490 : 205/65-10 Galvanized 5H/Eply Assembly FREE SHIPPING
to 48 Continental US States!!!!

[Read More](#)

SKU: 3H490

Categories: [10"](#)

Product Description

- ST205/65-10 E ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias10 Ply
- Load Range E, 1660# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 90
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6" Galvanized Finish
 - 0 offset
 - 5H x 4.5" Bolt Pattern
-



205/65-10 White 4H/Cply Assembly

3H370 : 205/65-10 White 4H/Cply Assembly FREE SHIPPING to 48 Continental US States!!!!

[Read More](#)

SKU: 3H370

Categories: [10"](#)

Product Description

- ST205/65-10 C ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias Ply
- Load Range C, 1105# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 50
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6"
 - 0 offset
 - 4H x 4" Bolt Pattern
-



205/65-10 White 4H/Dply Assembly

3H410 : 205/65-10 White 4H/Dply Assembly FREE SHIPPING to 48 Continental US States!!!!

[Read More](#)

SKU: 3H410

Categories: [10"](#)

Product Description

- ST205/65-10 D ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias Ply
- Load Range D, 1330# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 70
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6"
 - 0 offset
 - 4H x 4" Bolt Pattern
-



205/65-10 White 4H/Eply Assembly

3H460 : 205/65-10 White 4H/Eply Assembly FREE SHIPPING to 48 Continental US States!!!!

[Read More](#)

SKU: 3H460

Categories: [10"](#)

Product Description

- ST205/65-10 E ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias10 Ply
- Load Range E, 1660# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 90
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6"
 - 0 offset
 - 4H x 4" Bolt Pattern
-



205/65-10 White 5H/Cply Assembly

3H390: 205/65-10 White 5H/Cply Assembly FREE SHIPPING to 48 Continental US States!!!!

[Read More](#)

SKU: 3H390

Categories: [10"](#)

Product Description

- ST205/65-10 C ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias Ply
- Load Range C, 1105# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 50
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6"
 - 0 offset
 - 5H x 4.5" Bolt Pattern
-



205/65-10 White 5H/Dply Assembly

3H430 : 205/65-10 White 5H/Dply Assembly FREE SHIPPING to 48 Continental US States!!!!

[Read More](#)

SKU: 3H430

Categories: [10"](#)

Product Description

- ST205/65-10 D ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias Ply
- Load Range D, 1330# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 70
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6"
 - 0 offset
 - 5H x 4.5" Bolt Pattern
-



205/65-10 White 5H/Eply Assembly

3H480 : 205/65-10 White 5H/Eply Assembly FREE SHIPPING to 48 Continental US States!!!!

[Read More](#)

SKU: 3H480

Categories: [10"](#)

Product Description

- ST205/65-10 E ply LoadStar K399
- 20.5/8.0-10 Alternate Size
- High Speed Trailer Tire
- Tubeless type
- Bias10 Ply
- Load Range E, 1660# capacity
- S.W: 8.3"
- O.D: 20.7"
- Max PSI 90
- Rim 10x6
- The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.

Rim Specs:

- 10" x 6"
 - 0 offset
 - 5H x 4.5" Bolt Pattern
-



DUAL 4.75" Elevate ST235/80R16 DUAL SILVER 8H/E Assembly

ST235/80R16 Steel Silver Dual / Bud 4.75" 8H/E Assembly

[Read More](#)

SKU: D2E34945

Categories: [16"](#)

Product Description

Completely Assembled Unit

Tire: ST235/80R16 Eply mated to a 16"x6" 8 on 6.5" Hole Bolt Pattern SILVER DUALY Rim, 3100# capacity assembly

Tire Specs:

- Elevate ST235/80R16 Eply 10PLY
- High Speed Trailer Tire
- Tubeless Type
- Radial Ply
- Load Range E, 3500# capacity
- S.W: 9.4"
- O.D: 30.9"
- Max PSI 90
- Rim
16x6
n

&



ELEVATE ST225/75R15 6H/D ply Silver Mod Trailer Wheel Assembly

ELEVATE ST225/75R15 6H/D ply Silver Mod Hole Radial Trailer
Wheel Assembly

[Read More](#)

SKU: Y306130

Categories: [15"](#)

Product Description

- **Tire Specs**
 - **RADIAL**
 - **ELEVATE ST225/75R15 Dply (8 PLY)**
 - H78x15 Alternate Size
 - High Speed Trailer Tire
 - Tubeless Type
 - Radial Ply
 - Load Range D, 2540# capacity
 - S.W: 8.9"
 - O.D: 28.4"
 - Max PSI 65
 - Rim 15x6
 - The LoadStar Trailer tire provides a 2 year warranty with the warranty number imprinted on each tire.
 - These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
 -
 -
 -
 - Rim Specs
 - 15"x6" SILVER MOD HOLE Steel Rim Powder Coated
 - Bolt Pattern 6 x 5.5"
 - Rim Capacity & PSI 2830# / 80PSI
 - 0 offset
 - 4.27" Pilot Diameter
-



ELEVATE STR RADIAL ST205/75R15 Aluminum / Gun Metal Wheel Assembly 5H x 4.5" BP

15" Aluminum / Gun Metal Wheel / Tire Assembly 5H x 4.5" BP

[Read More](#)

SKU: Y305009-053

Categories: [15"](#)

Product Description

- Tire Specs
- Radial Ply
- ST205/75R15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Speed Rating M / 81 Mph
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- Wide center rib for improved road contact
- Open shoulder tread pattern to improve self-cleaning abilities
- Enhanced tread blade design to reduce scrubbing when turning
- Improved heat dissipation to extend the tread life
- Down To Earth Factory OEM Tire.
- Rim Specs:
 - 15"x5" 1 Piece Aluminum
 - Clear Coated Rim
 - Bolt Pattern 5 x 4.5"
 - Pilot Diameter 3.19"

- Rim Capacity 2150#
 - 0 offset
 - 5) Acorn Lug Nuts
 - 1) Center Cap
-



GOODRIDE Bias ST205/75D15 5H/C ply Gloss BLACK MOD HOLE Trailer Wheel Assembly

GOODRIDE ST205/75D15 5H/C ply Gloss BLACK MOD HOLE Bias Trailer Wheel Assembly !

[Read More](#)

SKU: D2E9400303-TT-1

Categories: [15"](#)

Product Description

- **Tire Specs**
- **BIAS PLY**
- GOODRIDE ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 8.1"
- O.D. 27.3"
- Max PSI 50
- RIM 15x5.5
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- Down To Earth Factory OEM Tire.
-
-
-
- **Rim Specs**
- 15"x5" BLACK Spoke Steel Rim, Powder Coated
- Bolt Pattern 5 x 4.5"

- Rim Capacity & PSI 1820# / 50PSI
- 0 offset
- 3.19" Pilot Diameter



GOODRIDE Radial ST205/75R15 5H/C ply Gloss BLACK Trailer Wheel Assembly

D2E9400303-TT : GOODRIDE ST205/75R15 5H/C ply Gloss
BLACK Radial Trailer Wheel Assembly !

[Read More](#)

SKU: D2E9400303-TT

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL**
- GOODRIDE LOADSTAR KARRIER ST205/75R15 C ply (6 ply)
- F78x15 Alternate Size
- •High Speed Trailer Tire
- •Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 8.1"
- O.D. 27.3"
- Max PSI 50
- RIM 15x5.5
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 5 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.
-
-
-
- **Rim Specs**

- 15"x5" BLACK Spoke Steel Rim, Powder Coated
 - Bolt Pattern 5 x 4.5"
 - Rim Capacity & PSI 1820# / 50PSI
 - 0 offset
 - 3.19" Pilot Diameter
-



GOODRIDE Radial ST225/75R15 6H/D ply Gloss BLACK MOD Trailer Wheel Assembly

D2E9400407-TT : LoadStar ST225/75R15 6H/D ply Gloss BLACK MOD HOLE Radial Trailer Wheel Assembly !

[Read More](#)

SKU: D2E9400407-TT

Categories: [15"](#)

Product Description

- **Tire Specs**
- **RADIAL**
- **GOODRIDE RADIAL ST225/75R15 Dply (8 PLY)**
- H78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Radial Ply
- Load Range D, 2540# capacity
- S.W: 8.9"
- O.D: 28.4"
- Max PSI 65
- Rim 15x6
- The GOODRIDE Trailer tire provides a 5 year warranty with the warranty number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Rim Specs
- 15"x6" Black Mod Hole Steel Rim Powder Coated

- Bolt Pattern 6 x 5.5"
 - Rim Capacity & PSI 2830# / 80PSI
 - 0 offset
 - 4.27" Pilot Diameter
-



GOODRIDE Radial ST235/80R16 Steel BLACK Modular Hole 8H/E Assembly

ST235/80R16 Steel BLACK Modular Hole 8H/E Assembly

[Read More](#)

SKU: D2E9400869-TT

Categories: [16"](#)

Product Description

Completely Assembled Unit

Tire: ST235/80R16 Eply mated to a 16"x6" 8 on 6.5" Hole Bolt Pattern BLACK PAINTED Steel Modular Hole Rim, 3500# capacity assembly

Tire Specs:

- GOODRIDE Radial Tire ST235/80R16 Eply 10PLY
- High Speed Trailer Tire
- Tubeless Type
- Radial Ply
- Load Range E, 3500# capacity
- S.W: 9.4"
- O.D: 30.9"
- Max PSI 90
- Rim
16x6

- **Rim Specs**

- 16"x6" BLACK Modular Hole
- Bolt Pattern 8 x 6.5"
- Pilot Diameter
- Rim Capacity & PSI 3750# / 110PSI
- 0 offset

- 4.90" Pilot Diameter
-



KENDA LOADSTAR K550 ST205/75D15 Aluminum 5 Star Wheel / Tire Assembly 5H x 4.5" BP

15" Aluminum 5 Star Wheel / Tire Assembly 5H x 4.5" BP !

[Read More](#)

SKU: D2E3S649

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.
 - Rim Specs:
 - - 15"x6" 1 Piece Aluminum
 - Clear Coated Rim
 - Bolt Pattern 5 x 4.5"
 - Pilot Diameter 3.19"
 - Rim Capacity 2150#
 - 0 offset



KENDA LOADSTAR K550 ST205/75D15 Aluminum 7 Star Wheel / Tire Assembly 5H x 4.5" BP

15" Aluminum 7 Star Wheel / Tire Assembly 5H x 4.5" BP

[Read More](#)

SKU: D2E3S264

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.
 - Rim Specs:
 - 15"x6" 1 Piece Aluminum
 - Clear Coated Rim
 - Bolt Pattern 5 x 4.5"
 - Pilot Diameter 3.19"
 - Rim Capacity 2150#
 - 0 offset



KENDA LOADSTAR K550 ST205/75D15 Aluminum Split Spoke Wheel / Tire Assembly 5H x 4.5" BP

15" Aluminum Split Spoke Wheel / Tire Assembly 5H x 4.5" BP

[Read More](#)

SKU: D2E3S740HWT

Categories: [15"](#)

Product Description

- Tire Specs
- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.8"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.
 - Rim Specs:
 - 15"x6" 1 Piece Aluminum
 - Clear Coated Rim
 - Bolt Pattern 5 x 4.5"
 - Pilot Diameter 3.19"
 - Rim Capacity 2150#
 - 0 offset



KENDA LOADSTAR K550 ST205/75D15 5Hon4.5"/C ply MODULAR HOLE ALUMINUM Trailer Wheel Assembly

D2E3S644 : LoadStar K550 Bias ST205/75D15 5Hon4.5"/C ply
MODULAR HOLE ALUMINUM Trailer Wheel Assembly

[Read More](#)

SKU: D2E3S644

Categories: [15"](#)

Product Description

- **Tire Specs:**

- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
- F78x15 Alternate Size
- High Speed Trailer Tire
- Tubeless Type
- Load Range C, 1820# capacity
- Sidewall 7.6"
- O.D. 27.4"
- Max PSI 50
- Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
- The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
- These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
- Down To Earth Factory OEM Tire.

- **Rim Specs:**

- 15"x6" 1 Piece Aluminum MOD HOLE
- Clear Coated Rim
- Bolt Pattern 5 x 4.5"
- Pilot Diameter 3.19"
- Rim Capacity 2150#
- 0 offset



KENDA LOADSTAR K550 ST205/75D15 5Hon5"/C ply White Spoke Trailer Wheel Assembly

LoadStar K550 ST205/75D15 Cply mounted to 15"x5" White Spoke Rim featuring 5 on 5" Bolt Pattern.

[Read More](#)

SKU: D2E3S638

Categories: [15"](#)

Product Description

- KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
 - F78x15 Alternate Size
 - High Speed Trailer Tire
 - Tubeless Type
 - Load Range C, 1820# capacity
 - Sidewall 7.8"
 - O.D. 27.4"
 - Max PSI 50
 - Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
 - The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
 - These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
 - Down To Earth Factory OEM Tire.

 - Rim Specs
 - 15"x5" White Spoke Steel Rim Powder Coated w/ Red/Blue Pinstripe &
 - Bolt Pattern 5 x 5"
 - Rim Capacity & PSI 1820# / 50PSI
 - 0 offset
 - 3.19" Pilot Diameter
-



KENDA LOADSTAR K550 ST205/75D15 BLACK Spoke 5Hx4.5/C Assembly

KENDA LOADSTAR K550 ST205/75D15 BLACK Spoke 5Hx4.5/C
Assembly

[Read More](#)

SKU: D2E3S651

Categories: [15"](#)

Product Description

- Tire Specs
 - KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
 - F78x15 Alternate Size
 - •High Speed Trailer Tire
 - •Tubeless Type
 - Load Range C, 1820# capacity
 - Sidewall 7.8"
 - O.D. 27.4"
 - Max PSI 50
 - Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
 - The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
 - These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
 - Down To Earth Factory OEM Tire.
-
- Rim Specs
 - 15"x5" BLACK Spoke Steel Rim, Powder Coated
 - Bolt Pattern 5 x 4.5"
 - Rim Capacity & PSI 1820# / 50PSI
 - 0 offset
 - 3.19" Pilot Diameter
-



KENDA LOADSTAR K550 ST205/75D15 Galvanized Trailer Wheel / Tire Assembly 5H x 4.5" Cply

15" Galvanized Trailer Wheel / Tire Assembly 5H x 4.5" Cply

[Read More](#)

SKU: D2E3S650

Categories: [15"](#)

Product Description

- Tire Specs
 - KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
 - F78x15 Alternate Size
 - High Speed Trailer Tire
 - Tubeless Type
 - Load Range C, 1820# capacity
 - Sidewall 7.8"
 - O.D. 27.4"
 - Max PSI 65
 - Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
 - The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
 - These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
 - Down To Earth Factory OEM Tire.

 - Rim Specs
 - 15"x6" Galvanized Spoke Steel Rim
 - Rim Capacity & PSI 2050# @ 75 PSI
 - 0 offset
 - 3.19" Pilot Diameter
-



KENDA LOADSTAR K550 ST205/75D15 Silver Mod 5Hon5" /C Assembly

D2E32253 : Loadstar K550 ST205/75D15 Silver Mod 5Hon5"/C
Assembly

[Read More](#)

SKU: D2E32253

Categories: [15"](#)

Product Description

- Tire Specs
 - KENDA LOADSTAR K550 ST205/75D15 C ply (6 ply)
 - F78x15 Alternate Size
 - High Speed Trailer Tire
 - Tubeless Type
 - Load Range C, 1820# capacity
 - Sidewall 7.8"
 - O.D. 27.4"
 - Max PSI 50
 - Nylon Bias Ply Constructed Tire for Durability and Bruise Resistance.
 - The LoadStar Trailer tire provides a 2 year warranty with the warranty Phone number imprinted on each tire.
 - These tires provide: Longer Wear, Better Towing Stability, Reduced Rolling Resistance and meets all US Dept of Transportation requirements.
 - Down To Earth Factory OEM Tire.
-
- Rim Specs
 - 15"x5" Silver Modular Hole Steel Rim, Powder Coated
 - Bolt Pattern 5 x 5"
 - Rim Capacity & PSI 1820# / 50PSI
 - 0 offset
 - 3.19" Pilot Diameter
-